



TONNEAU INSTALATION INSTRUCTIONS  
HQ-HJ-HX-HZ-WB TONNEAU, 1971-1984  
Part number: 205

**CONTENTS**

1 X Tonneau cover

1 X 1 Tonneau lock kit including 2 large rivets

Checked by \_\_\_\_\_

Date \_\_\_\_\_

**CARING FOR YOUR TONNEAU**

Apply bee's wax or Dri-lube to stitching a few times a year, as this will maintain the tonneau's waterproofing ability and prevent the stitching from degrading. Use a mild detergent and soft scrubbing brush to clean tonneau.

**Never drive without tonneau support bars in place as flapping can cause a delaminating effect on the material.**

"Tonneau is not designed to be used as a load restraint"

# Tonno Lock



## INTRODUCTION

The Tonno Lock is now a standard feature included with all Tuff Tonneaus. The Tonno Lock is situated at the front of the tonneau cover, so as not to impede the accessibility of the Tuff Tonneau.

Fitting the lock is simple and only requires a small attachment on the inside edge of the tub behind the cab. Together with a padlock, it provides you with an extremely effective theft deterrent. The Tonno Lock is designed to suit all utes and prevent thieves stealing your Tuff Tonneau, so you can continue to rely on the Tuff Tonneaus' name to give you what you want in a tonneau cover.

## BASIC TOOLS REQUIRED

Rivet gun, Drill, Torch, Marking Pencil/Pen. You will need to buy a small Padlock- make sure the padlock will go through the hole on the Tonno lock.

## TONNO LOCK CONTENTS

2 X 4MM Aluminium rivets  
1 x Black Tonno Lock bracket

## FITTING TONNO LOCK

1. Attach the black lock bracket to the bracket on the tonneau with your padlock, and fit the tarp.
2. Getting under the tarp with a torch, place the lock bracket against the body and mark holes with a pen.
3. Remove tonneau and drill the marks with a 4 mm drill bit, place the lock bracket in position and rivet.

**Your Tuff Tonneau is now ready for work.**